



- NOTES:**
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=± 0.4  
X.XX=± 0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  4. RATING: 12VDC, 12mA; SPST
  5. CONTACT MATERIAL: GOLD
  6. CONTACT RESISTANCE: 50 MILLI-OHM MAX.
  7. INSULATION RESISTANCE: 500VDC, 100 MEGA-OHM MIN.
  - ▲8. OPERATING FORCE: 150± 100GF
  9. OPERATING LIFE: 200,000 CYCLES
  10. OPERATING TEMP: -20°C TO +70°C
  - ▲11. LED COLORS: RED, GREEN
  12. TRAVEL: 2.20mm±0.20
  13. 2002/95/EC (ROHS) COMPLIANT
  14. ▲DENOTES CRITICAL PARAMETER.

▲ LED SPECS	UNITS	RED	GREEN
FORWARD CURRENT	mA	25	25
FORWARD VOLTAGE @20mA	VDC	1.95	2.0
LUMINOUS INTENSITY @ 10mA	mcd	77	412



B	19589	CHANGED DIMS: was 15.6 & 5.07	1/14/11	BGL
A	18147	New Release	6/18/08	rc
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE LP60A1ASRG				
SCALE	DATE	DR	DWG	REV
2=1	6/18/2008	rc	B220001	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED